



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

Section 1. Identification

Product Identity	Liquid Bearing Gasoline Conditioner
Relevant identified uses of the substance	Gasoline fuel additive
Details of the supplier of the safety data sheet	
Company Name	Formula Lubricants #12 - 11191 Horseshoe Way, Richmond, BC V7A 4S5
Customer Service:	604-808-5601
Emergency:	1-888-CAN-UTEC (for transport only)

Section 2. Hazard(s) identification

Classification of the substance or mixture under US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

Flammable Liquid, category 3;H226	Flammable liquid and vapor.
Carcinogen, category 2;H351	Suspected of causing cancer.
Aspiration hazard, category 1;H304	May be fatal if swallowed and enters airways.
Aquatic toxicity (acute), category 3;H402	Harmful to aquatic life.
Aquatic toxicity (chronic), category 3;H412	Harmful to aquatic life with long lasting effects.

Label elements



Danger

H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H351 Suspected of causing cancer.
H412 Harmful to aquatic life with long lasting effects.

[Prevention]

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.
P233 Keep container tightly closed.
P240 Ground, bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating, light, equipment.
P242 Use only non-sparking tools.



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

- P243 Take action to prevent static discharges.
P260 Do not breathe dust, fume, mist, vapors or spray.
P262 Do not get in eyes, on skin, or on clothing.
P273 Avoid release to the environment.
P280 Wear protective gloves, eye protection, and face protection.

[Response]

- P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.
P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.
P308+313 IF exposed or concerned: Get medical advice or attention.
P331 Do NOT induce vomiting.
P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]

- P403+235 Store in a well ventilated place. Keep cool.
P405 Store locked up.

[Disposal]

- P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

- This product contains PBT/vPvB/vPvM chemicals.
This product contains no endocrine disrupting chemicals.

Does not contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per US or Canadian regulations.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Cas number	Synonym	Weight %
Hydrocarbon Solvent	64742-48-9	Hydrotreated heavy naphtha (petroleum), Naphtha (petroleum), hydrotreated heavy	45 - 70
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil-unspecified	72623-86-0	No available information	30 - 60
Tetradecane, chloro derivs.	198840-65-2	No available information	7 - 13
Naphtha (petroleum), heavy aromatic	64742-94-5	Solvent naphtha (petroleum), heavy aromatic	3 - 7
Naphthalene	91-20-3	Naphtalen	0.1 - 1



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

Section 4. First aid measures

Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause tearing, stinging, redness, irritation, and burns.

Inhalation: Irritating to respiratory tract. Prolonged or repeated breathing of very high vapor concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

Ingestion: Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

Skin Contact: Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

Signs and Symptoms Of Exposure: Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapors can cause effects to liver and kidneys.

Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation May be fatal if swallowed and enters airways.



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

Section 5. Fire-fighting measures

Extinguishing media

Suitable Extinguishing Media: Small Fire: Dry chemical, CO₂, water spray or regular foam. Large Fire: Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media: Do not use straight streams.

Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of carbon.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Keep container tightly closed.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Do not breathe dust, fume, mist, vapors or spray.

Do not get in eyes, on skin, or on clothing.

Advice for fire-fighters

Flammable liquid and vapor. Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

May cause toxic effects if inhaled or absorbed through skin. Inhalation or contact with material may irritate or burn skin and eyes. Fire will produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control or dilution water may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

ERG Guide No. 128

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

As an immediate precautionary measure, isolate spill or leak area. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded.

Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Methods and material for containment and cleaning up

Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. Large spills should be removed with explosion proof vacuum equipment.

Eliminate ignition sources. Soak up with noncombustible absorbent material. Remove absorbent material for proper disposal.



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Do not swallow. Do not breathe mist, vapours, or spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. See Section 8 for information on Personal Protective Equipment.

See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Limit quantity of material in storage. Restrict access to storage area. Post appropriate warning signs. Keep storage area separate from populated work areas. Consider leak detection and alarm systems, as required. Store in a well-ventilated place. Keep container tightly closed. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children. Head spaces in storage containers may contain toxic hydrogen sulphide gas. Structural materials and lighting and ventilation systems should be corrosion resistant.

Incompatible materials: Strong acids. Strong oxidizers.

Other Precautions: All labeled precautions must be observed when handling, storing and transporting empty containers due to product residues. Do not reuse containers. Empty containers may contain material residues which can ignite with explosive force. Cutting or welding of empty containers can cause fire, explosion, or release fumes from residues. Keep containers closed and drum bungs in place. Dispose of in a licensed facility.

See section 2 for further details. - [Storage]

Specific end use(s)

No data available

Section 8. Exposure controls / personal protection

Exposure Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
91-20-3	Naphthalene	ACGIH	10 ppm
		OSHA	10 ppm, 50 mg/m ³
		NIOSH	TWA 10 ppm (50 mg/m ³) STEL: 15 ppm (75 mg/m ³)
		Alberta	10 ppm TWA; 52 mg/m ³ TWA 15 ppm STEL; 79 mg/m ³ STEL
		British Columbia	10 ppm TWA
		Saskatchewan	10 ppm TWA 15 ppm STEL
64742-48-9	Hydrocarbon Solvent	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Saskatchewan	No Established Limit
64742-94-5	Naphtha (petroleum), heavy aromatic	ACGIH	No Established Limit
		OSHA	No Established Limit

		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Saskatchewan	No Established Limit
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil-unspecified	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Saskatchewan	No Established Limit
198840-65-2	Tetradecane, chloro derivs.	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Saskatchewan	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³ OSHA PEL and 5 mg/m³ ACGIH.

Exposure controls



Respiratory

If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4-18, with organic vapor cartridge and particulate filter, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

Eyes

Safety glasses with side shields required. Use chemical splash goggles if a splash hazard exists. Ensure that eyewash stations are close to the workstation location. Use equipment for eye protection that meets the standards referenced by OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.

Skin

Wear protective clothing. Flame resistant clothing that meets the NFPA 2112 and CAN/CGSB 155.20 standards is recommended in areas where material is stored or handled. Additional PPE, such as chemical aprons, may be required if product is used outside of intended use per manufacturer. Wear protective gloves that are chemically resistant to this material. Examples of acceptable glove materials include nitrile and viton. Consider the parameters specified by the glove manufacturer and check during use that the gloves are still retaining their protective properties.

Engineering Controls

Use outdoors or with ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below recommended exposure limits. Use explosion-proof electrical, ventilating, and lighting equipment.

Other Work Practices

Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Liquid
Color	Colorless
Odor	Not Available
Melting point / freezing point	Not Available
Initial boiling point and boiling range	176.3 °C ASTM D-86
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Available Upper Explosive Limit: Not Available
Flash Point	60 °C ASTM D-93
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
pH	Not Available
Viscosity (cSt)	3.8 cSt at 40 °C
Solubility in Water	Not Available
Partition coefficient n-octanol/water (Log Kow)	Not Available
Vapor pressure (Pa)	Not Available
Relative Density	0.8325 g/cm ³
Vapor Density	Not Available
Evaporation rate (Ether = 1)	Not Available
VOC Content	Not Available
Other information	
DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)	

Section 10. Stability and reactivity

Reactivity	Hazardous Polymerization will not occur.
Chemical stability	Stable under normal circumstances.
Possibility of hazardous reactions	No data available.
Conditions to avoid	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Incompatible materials	Strong acids. Strong oxidizers.
Hazardous decomposition products	Oxides of carbon.



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Hydrocarbon Solvent - (64742-48-9)	> 5,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil-unspecified - (72623-86-0)	No data available.	No data available.	No data available.	No data available.	No data available.
Tetradecane, chloro derivs. - (198840-65-2)	No data available.	No data available.	No data available.	No data available.	No data available.
Naphtha (petroleum), heavy aromatic - (64742-94-5)	> 5,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.
Naphthalene - (91-20-3)	490.00, Rat - Category: 4	20,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
91-20-3	Naphthalene	IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
		ACGIH	A3
7783-06-4	Hydrogen sulfide	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
64742-48-9	Hydrocarbon Solvent	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
64742-94-5	Naphtha (petroleum), heavy aromatic	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
72623-86-0	Lubricating oils (petroleum), C15- 30, hydrotreated neutral oil-based; Baseoil-unspecified	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
198840-65-2	Tetradecane, chloro derivs.	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	2	Suspected of causing cancer.
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	1	May be fatal if swallowed and enters airways.

Possible routes of entry: Inhalation, ingestion, skin contact and absorption.

Symptoms and effects, both acute and delayed:

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause tearing, stinging, redness, irritation, and burns.

Inhalation: Irritating to respiratory tract. Prolonged or repeated breathing of very high vapor concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

Ingestion: Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

Skin Contact: Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

Signs And Symptoms Of Exposure: Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapors can cause effects to liver and kidneys.

Treat symptomatically.

Section 12. Ecological information

Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Hydrocarbon Solvent - (64742-48-9)	18.00, Oncorhynchus mykiss	4.50, Daphnia magna	3.10, Pseudokirchneriella subcapitata
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil-unspecified - (72623-86-0)	No data available.	No data available.	No data available.
Tetradecane, chloro derivs. - (198840-65-2)	No data available.	No data available.	No data available.
Naphtha (petroleum), heavy aromatic - (64742-94-5)	45.00, Pimephales promelas	12.00, Daphnia magna	2.50, Skeletonema costatum
Naphthalene - (91-20-3)	0.99, Oncorhynchus gorbuscha	1.60, Daphnia magna	68.21, Scenedesmus subspicatus



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

Persistence and degradability	There is no data available on the preparation itself.
Bioaccumulative potential	Not Available
Mobility in soil	No data available.
Results of PBT and vPvB assessment	This product contains PBT/vPvB/vPvM chemicals.
Other adverse effects	No data available.

Section 13. Disposal considerations

Waste treatment methods

Waste should not be released to sewers. Observe all federal, state, and local regulations when disposing of this substance.

Section 14. Transport information

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

TDG (Domestic Surface Transportation)

UN number	UN1268
UN proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Transport hazard class(es)	3
Packing group	III

DOT (Domestic Surface Transportation)

UN number	UN1268
UN proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Transport hazard class(es)	3
Packing group	III

IMO / IMDG (Ocean Transportation)

UN number	UN1268
UN proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Transport hazard class(es)	IMDG: 3
Packing group	III

ICAO/IATA

UN number	UN1268
UN proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Transport hazard class(es)	Air Class: 3
Packing group	III

Environmental hazards

Marine Pollutant: No;



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

Special precautions for user

The flash point for this material is greater than 100 °F (38 °C). Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

This product has been classified in accordance with US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) (GHS revision 7) and the SDS contains all of the information required by those regulations.

Toxic Substance Control Act (TSCA)

1,2,3-Trimethylbenzene
1,2,4-trimethyl benzene
Benzene
Cumene
Hydrogen sulfide
Hydrocarbon Solvent (UVCB)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil-unspecified (UVCB)
Naphthalene
Naphtha (petroleum), heavy aromatic (UVCB)
Tetradecane, chloro derivs. (UVCB PMN; S; 5E)
White mineral oil (petroleum) (UVCB)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Naphthalene

Canadian Domestic Substance List (DSL):

1,2,3-Trimethylbenzene
1,2,4-trimethyl benzene
Benzene
Cumene
Hydrogen sulfide
Hydrocarbon Solvent
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Base oil-unspecified
Naphthalene
Naphtha (petroleum), heavy aromatic
White mineral oil (petroleum)



Safety Data Sheet Liquid Bearing Gasoline Conditioner

Revision Date: 09/09/2026

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

Benzene

Cumene

Naphthalene

Proposition 65 - Developmental Toxins (>0.0%):

Benzene

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

Benzene

Proposition 65 Label Warning:



WARNING: This product can expose you to chemicals including [Benzene, Cumene, Naphthalene], which are known to the State of California to cause cancer, and [Benzene], which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16. Other information

Revision Date September 9, 2026

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

SDS authored by Chemscape (403-720-3700)

End of Document